

SAFETY DATA SHEET

Bug and Tar Remover

Section 1. Identification

GHS product identifier : Medium Degreaser / Bug and Tar Remover
Product code : BTR
Other means of identification : Not available.
Product type : Liquid.

Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Medium cleaner degreaser / Bug and tar Remover.

Supplier's details : Nexgen Global LLC

3753 Howard Hughes Parkway, Suite 200
Las Vegas, Nevada 89169

(386) 957-1857
support@getnexgen.com

Emergency telephone number (with hours of operation) : CHEMTREC, U.S.: 1-800-424-9300 International: +1-703-527-3887
24/7

Section 2. Hazards identification

OSHA/HCS status : Note: This product is a consumer product and is labeled in accordance with the Consumer Product Safety Commission regulations and NOT OSHA Regulations. The requirements for the labeling consumer products takes precedent over OSHA labeling so the actual product label will not contain OSHA label elements shown below on this SDS

Classification of the substance or mixture

Signal word, hazard statement(s), symbol(s) and precautionary statements in accordance with (29 CFR 1910.1200).

GHS label elements

Hazard pictograms

SKIN CORROSION/IRRITATION Category 1A
SERIOUS EYE DAMAGE/ EYE IRRITATION Category 1
AQUATIC HAZARD (ACUTE) Category 3
AQUATIC HAZARD (LONG-TERM) Category 3

Signal word : Danger

Hazard statements : H314 - Causes severe skin burns and eye damage.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

: P280 - Wear protective gloves. Wear eye or face protection. Wear protective clothing.
P273 - Avoid release to the environment.
P264 - Wash hands thoroughly after handling.



Bug and Tar Remover

Section 2. Hazards identification

- Response** : P304 + P340 + P310 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or physician.
P301 + P310 + P330 + P331 - IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. Do NOT induce vomiting.
P303 + P361 + P353 + P363 + P310 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. Wash contaminated clothing before reuse. Immediately call a POISON CENTER or physician.
P305 + P351 + P338 + P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or physician.
- Storage** : P405 - Store locked up.
- Disposal** : P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Supplemental label elements** : Do not taste or swallow. Wash thoroughly after handling.
- Hazards not otherwise classified** : Causes digestive tract burns.

Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

| Ingredient name | % | CAS number |
|------------------------------|----------|------------|
| Sodium hydroxide | ≥5 - ≤10 | 1310-73-2 |
| 2-Butoxyethanol | ≥5 - ≤10 | 111-76-2 |
| Nonylphenol, ethoxylated | ≥3 - ≤5 | 9016-45-9 |
| Sodium xylenesulphonate | ≥3 - ≤5 | 1300-72-7 |
| Dodecylbenzenesulphonic acid | ≥1 - ≤3 | 27176-87-0 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.



Section 4. First aid measures

- Skin contact** : Get medical attention immediately. Call a poison center or physician. Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes. Chemical burns must be treated promptly by a physician. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
- Skin contact** : Causes severe burns.
- Ingestion** : Corrosive to the digestive tract. Causes burns. May cause burns to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing media : Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing media : None known.

Specific hazards arising from the chemical : In a fire or if heated, a pressure increase will occur and the container may burst. This material is harmful to aquatic life with long lasting effects. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
sulfur oxides
metal oxide/oxides

Special protective actions for fire-fighters : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders : If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Water polluting material. May be harmful to the environment if released in large quantities.

Methods and materials for containment and cleaning up

Spill : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Avoid release to the environment. If during normal use the material presents a respiratory hazard, use only with adequate ventilation or wear appropriate respirator. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|---|---|
| Sodium hydroxide | ACGIH TLV (United States, 3/2017). CEIL: 2 mg/m ³ |
| 2-Butoxyethanol | NIOSH REL (United States, 10/2016). CEIL: 2 mg/m ³ OSHA PEL (United States, 6/2016). TWA: 2 mg/m ³ 8 hours. ACGIH TLV (United States, 3/2017). TWA: 20 ppm 8 hours. NIOSH REL (United States, 10/2016). Absorbed through skin. TWA: 5 ppm 10 hours. TWA: 24 mg/m ³ 10 hours. OSHA PEL (United States, 6/2016). Absorbed through skin. TWA: 50 ppm 8 hours. TWA: 240 mg/m ³ 8 hours. |
| Nonylphenol, ethoxylated Sodium xylenesulphonate Dodecylbenzenesulphonic acid | None. None. None. |

- Appropriate engineering controls** : If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 8. Exposure controls/personal protection

- Eye/face protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.
- Skin protection**
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** : Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use.

Section 9. Physical and chemical properties

Appearance

- Physical state** : Liquid.
- Color** : Neon yellow / Green
- Odor** : Butyl / Ammoniated
- Odor threshold** : Not available.
- pH** : >12
- Melting point** : Not available.
- Boiling point** : >93.33°C (>200°F)
- Flash point** : Closed cup: 93.333°C (200°F) [Pensky-Martens.]
- Evaporation rate** : Not available.
- Flammability (solid, gas)** : Not available.
- Lower and upper explosive (flammable) limits** : Not available.
- Vapor pressure** : >0.13 kPa (>1 mm Hg) [room temperature]
- Vapor density** : >1 [Air = 1]
- Relative density** : 0.986 to 1.15
- Solubility** : Completely miscible in water.
- Partition coefficient: n-octanol/water** : Not available.
- Auto-ignition temperature** : Not available.
- Decomposition temperature** : Not available.
- Viscosity** : Not available.
- Flow time (ISO 2431)** : Not available. :
- VOC (w/w)** : 5% w/w / 46.49 g/L

Bug and Tar Remover

Section 10. Stability and reactivity

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- Conditions to avoid** : No specific data.
- Incompatible materials** : Reactive or incompatible with the following materials: oxidizing materials.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|------------------------------|-----------|---------|-----------|----------|
| 2-Butoxyethanol | LD50 Oral | Rat | 917 mg/kg | - |
| Dodecylbenzenesulphonic acid | LD50 Oral | Rat | 650 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|------------------------------|--------------------------|------------|-------|-----------------------------|-------------|
| Sodium hydroxide | Eyes - Mild irritant | Rabbit | - | 400 µg | - |
| | Eyes - Severe irritant | Rabbit | - | 24 hours 50 µg | - |
| | Eyes - Severe irritant | Rabbit | - | 1% | - |
| | Eyes - Severe irritant | Rabbit | - | 0.5 minutes 1 mg | - |
| | Skin - Severe irritant | Rabbit | - | 24 hours 500 mg | - |
| 2-Butoxyethanol | Eyes - Moderate irritant | Rabbit | - | 24 hours 100 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 100 mg | - |
| | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| Nonylphenol, ethoxylated | Eyes - Severe irritant | Guinea pig | - | 20 mg | - |
| | Eyes - Severe irritant | Mouse | - | 20 mg | - |
| | Eyes - Severe irritant | Rabbit | - | 20 mg | - |
| | Skin - Mild irritant | Human | - | 72 hours 15 mg Intermittent | - |
| Dodecylbenzenesulphonic acid | Skin - Mild irritant | Rabbit | - | 500 mg | - |
| | Skin - Severe irritant | Rabbit | - | 0.5 ml | - |

Sensitization

There is no data available.

Mutagenicity

There is no data available.

Carcinogenicity

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| 2-Butoxyethanol | - | 3 | - |

Reproductive toxicity

There is no data available.

Teratogenicity

There is no data available.

Section 11. Toxicological information

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

There is no data available.

Information on the likely routes of exposure : Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

- Eye contact** : Causes serious eye damage.
- Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system.
- Skin contact** : Causes severe burns.
- Ingestion** : Corrosive to the digestive tract. Causes burns. May cause burns to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
pain
watering
redness
- Inhalation** : No known significant effects or critical hazards.
- Skin contact** : Adverse symptoms may include the following:
pain or irritation
redness
blistering may occur
- Ingestion** : Adverse symptoms may include the following:
stomach pains

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Long term exposure

- Potential immediate effects** : No known significant effects or critical hazards.
- Potential delayed effects** : No known significant effects or critical hazards.

Potential chronic health effects

- General** : No known significant effects or critical hazards.
- Carcinogenicity** : No known significant effects or critical hazards.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : No known significant effects or critical hazards.

Numerical measures of toxicity



Bug and Tar Remover

Section 11. Toxicological information

Acute toxicity estimates

| Route | ATE value |
|---------------------|-------------|
| Oral | 13446 mg/kg |
| Dermal | 22000 mg/kg |
| Inhalation (vapors) | 220 mg/L |

Section 12. Ecological information

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|---------------------------------|--------------------------------------|--|----------|
| Sodium hydroxide | Acute EC50 40.38 mg/L Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| 2-Butoxyethanol | Acute LC50 125 ppm Fresh water | Fish - Gambusia affinis - Adult | 96 hours |
| | Acute EC50 >1000 mg/L Fresh water | Daphnia - Daphnia magna | 48 hours |
| | Acute LC50 800000 µg/L Marine water | Crustaceans - Crangon crangon | 48 hours |
| Nonylphenol, ethoxylated | Acute LC50 1250000 µg/L Marine water | Fish - Menidia beryllina | 96 hours |
| | Acute EC50 12 mg/L Fresh water | Algae - Pseudokirchneriella subcapitata | 96 hours |
| | Acute LC50 1.23 mg/L Marine water | Crustaceans - Americamysis bahia | 48 hours |
| | Acute LC50 4800 µg/L Fresh water | Daphnia - Daphnia pulex - Larvae | 48 hours |
| | Acute LC50 1300 µg/L Fresh water | Fish - Lepomis macrochirus | 96 hours |
| Chronic NOEC 8 mg/L Fresh water | Chronic NOEC 8 mg/L Fresh water | Algae - Pseudokirchneriella subcapitata | 96 hours |
| | Chronic NOEC 105 µg/L Fresh water | Fish - Oryzias latipes - Fry | 100 days |

Persistence and degradability

There is no data available.

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|------------------------------|--------------------|-----|-----------|
| 2-Butoxyethanol | 0.81 | - | low |
| Sodium xylenesulphonate | -3.12 | - | low |
| Dodecylbenzenesulphonic acid | 4.78 | - | high |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods : The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling empty containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Bug and Tar Remover

Section 14. Transport information

| | DOT Classification | IMDG | IATA |
|-----------------------------------|---|---|---|
| UN number | UN3266 | UN3266 | UN3266 |
| UN proper shipping name | CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide) | CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide) | CORROSIVE LIQUID, BASIC, INORGANIC, N.O.S. (Sodium hydroxide) |
| Transport hazard class(es) | 8 Land transport (DOT) | 8 Land transport (DOT) | 8 Land transport (DOT) |
| Packing group | II | II | II |
| Environmental hazards | No. | No. | No. |

AERG : 154

DOT-RQ Details : Sodium hydroxide 1000 lbs / 454 kg

Additional information

DOT Classification : **Reportable quantity** 14285.7 lbs / 6485.7 kg [1604.3 gal / 6072.8 L]. Package sizes shipped in quantities less than the product reportable quantity are not subject to the RQ (reportable quantity) transportation requirements.

IMDG : **Emergency schedules** F-A, S-B

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Section 15. Regulatory information

U.S. Federal regulations : **TSCA 5(a)2 final significant new use rules:** Nonylphenol, ethoxylated
TSCA 8(a) PAIR: Nonylphenol, ethoxylated
TSCA 8(a) CDR Exempt/Partial exemption: Not determined
TSCA 12(b) one-time export: Nonylphenol, ethoxylated
United States inventory (TSCA 8b): All components are listed or exempted.
Clean Water Act (CWA) 311: Sodium hydroxide; Dodecylbenzenesulphonic acid

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Not listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Bug and Tar Remover

Section 15. Regulatory information

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : SKIN CORROSION/IRRITATION - Category 1A
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1
HNOC - Corrosive to digestive tract

Composition/information on ingredients

| Name | Classification |
|------------------------------|--|
| Sodium hydroxide | SKIN CORROSION/IRRITATION - Category 1A SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 HNOC - Corrosive to digestive tract |
| 2-Butoxyethanol | FLAMMABLE LIQUIDS - Category 4 ACUTE TOXICITY (oral) - Category 4 ACUTE TOXICITY (dermal) - Category 4 ACUTE TOXICITY (inhalation) - Category 4 SKIN CORROSION/IRRITATION - Category 2 |
| Nonylphenol, ethoxylated | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A SKIN CORROSION/IRRITATION - Category 2 |
| Sodium xylenesulphonate | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A |
| Dodecylbenzenesulphonic acid | SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A ACUTE TOXICITY (oral) - Category 4 SKIN CORROSION/IRRITATION - Category 1B SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 |

SARA 313

| | Product name | CAS number |
|--|-----------------|------------|
| Form R - Reporting requirements | 2-Butoxyethanol | 111-76-2 |
| Supplier notification | 2-Butoxyethanol | 111-76-2 |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: Sodium hydroxide; 2-Butoxyethanol; Dodecylbenzenesulphonic acid
- New York** : The following components are listed: Sodium hydroxide; Dodecylbenzenesulphonic acid
- New Jersey** : The following components are listed: Sodium hydroxide; 2-Butoxyethanol; Dodecylbenzenesulphonic acid
- Pennsylvania** : The following components are listed: Sodium hydroxide; 2-Butoxyethanol; Dodecylbenzenesulphonic acid

California Prop. 65

No products were found.

Section 16. Other information

Procedure used to derive the classification

| Classification | Justification |
|---|--------------------|
| SKIN CORROSION/IRRITATION - Category 1A | Calculation method |
| SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1 | Calculation method |
| AQUATIC HAZARD (ACUTE) - Category 3 | Calculation method |
| AQUATIC HAZARD (LONG-TERM) - Category 3 | Calculation method |

History

Section 16. Other information

Date of issue mm/dd/yyyy : 04/15/2018
Date of previous issue : 03/15/2014
Version : 2
Prepared by : KMK Regulatory Services Inc.

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

